



Revision Number: 009.1

Issue date: 05/14/2025

**1. IDENTIFICATION**

|                                       |  |           |                     |        |
|---------------------------------------|--|-----------|---------------------|--------|
| <b>Product name:</b>                  | <b>569 Thread Sealant Low Sealant Strength Hydraulic</b> | <b>ic</b> | <b>IDH number:</b>  | 135492 |
| <b>Product type/ Recommended use:</b> | Adhesive   |           | <b>Item number:</b> | 56931  |
| <b>Restriction of Use:</b>            | None identified  |           | <b>Region:</b>      | Canada |
| <b>Company address:</b>               | <b>Contact information:</b>                              |           |                     |        |
| Henkel Canada Corporation             | Telephone: +1 (905) 814-6511                             |           |                     |        |
| Meadowpine Boulevard 2515             | MEDICAL EMERGENCY Phone: Poison Control Center           |           |                     |        |
| Mississauga, Ontario L5N 6C3          | 1-877-671-4608 (toll free) or 1-303-592-1711             |           |                     |        |
|                                       | TRANSPORT EMERGENCY Phone: CHEMTREC                      |           |                     |        |
|                                       | 1-800-424-9300 (toll free) or 1-703-527-3887             |           |                     |        |
|                                       | MEDICAL EMERGENCY Phone: Poison Control Center           |           |                     |        |
|                                       | 1-877-671-4608 (toll free) or 1-303-592-1711             |           |                     |        |
|                                       | TRANSPORT EMERGENCY Phone: CHEMTREC                      |           |                     |        |
|                                       | 1-800-424-9300 (toll free) or 1-703-527-3887             |           |                     |        |
|                                       | Internet: www.henkelna.com                               |           |                     |        |

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** H315 - CAUSES SKIN IRRITATION.  
 H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.  
 H319 - CAUSES SERIOUS EYE IRRITATION.  
 H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| SKIN IRRITATION                                    | 2               |
| EYE IRRITATION                                     | 2A              |
| SKIN SENSITIZATION                                 | 1               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |

**PICTOGRAM(S)**



**Precautionary Statements**

|                    |   |
|--------------------|---|
| <b>Prevention:</b> | P260 - Do not breathe vapors, mist, or spray.<br>P264 - Wash affected area thoroughly after handling.<br>P272 - Contaminated work clothing should not be allowed out of the workplace.  |
| <b>Response:</b>   | P280 - Wear protective gloves, eye protection, and face protection.<br>P302+P352 - IF ON SKIN: Wash with plenty of water.<br>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P314 - Get medical attention if you feel unwell.<br>P333+P313 - If skin irritation or rash occurs: Get medical attention. |

IDH number: 135492

Product name: 569 Thread Sealant Low

ic Sealant Strength Hydraulic

**Storage:**  
**Disposal:**

P337+P313 - If eye irritation persists: Get medical attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
Not prescribed  
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Other hazards** Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)  | CAS Number | Weight %* |
|---|------------|-----------|
| Polyglycol dioctanoate  | 18268-70-7 | 10 - 30   |
| Methacrylic acid, isobutyl ester, polymer with butyl methacrylate | 9011-53-4  | 10 - 30   |
| Cumene hydroperoxide  | 80-15-9    | 1 - 5     |
| isobutyl methacrylate   | 97-86-9    | 0.1 - 1   |
| n-butyl methacrylate  | 97-88-1    | 0.1 - 1   |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

|  |   |
|--|---|
| <b>Inhalation:</b>   | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.                                      |
| <b>Skin contact:</b>   | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention. |
| <b>Eye contact:</b>  | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.   |
| <b>Ingestion:</b>  | Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.   |
| <b>Most important symptoms and effects (acute and delayed):</b>                  | The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.  |
| <b>Indication of any immediate medical attention / special treatment needed:</b> | Not available.  |

### 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Water spray (fog), foam, dry chemical or carbon dioxide.   |
| <b>Improper extinguishing agents:</b>     | Not available.   |
| <b>Special firefighting procedures:</b>   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| <b>Unusual fire or explosion hazards:</b> | Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.                                 |

**Hazardous combustion products:** Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

**Clean-up methods:** Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed. Refer to Section 8.

**Storage:** For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV  | OSHA PEL | AIHA WEEL                                     | OTHER |
|------------------------|------------|----------|---|-------|
| Cumene hydroperoxide   | None       | None     | 1 ppm (6 mg/m <sup>3</sup> )<br>TWA<br>(SKIN) | None  |
| methacrylic acid       | 20 ppm TWA | None     | None  | None  |

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Liquid  
**Color:** Brown  
**Odor:** Mild  
**Odor threshold:** Not available.  
**pH:** Not applicable, Product is non-polar/aprotic.  
**Vapor pressure:** < 0.13 mbar (20 °C (68°F))  
**Boiling point/range:** > 150 °C (> 302°F)None

|   |  |
|---|--|
| <b>Melting point/ range:</b>                                      | Not applicable, Product is a liquid  |
| <b>Density/Relative density:</b>                                  | 1.049  |
| <b>Relative vapor density:</b>                                    | > 1 20 °C  |
| <b>Flash point:</b>   | 156 °C (312.8 °F) Cleveland open cup > 100 °C (> 212°F) Tagliabue closed cup |
| <b>Flammable/Explosive limits - lower:</b>                        | Not available.   |
| <b>Flammable/Explosive limits - upper:</b>                        | Not available.   |
| <b>Autoignition temperature:</b>                                  | Not available.   |
| <b>Flammability:</b>  | The product is not flammable.  |
| <b>Evaporation rate:</b>  | Not available.   |
| <b>Solubility:</b>  | Slight Water   |
| <b>Partition coefficient n-octanol/water (logarithmic value):</b> | Not available.   |
| <b>VOC content:</b>   | 0.81 %; 7.74 g/l   |
| <b>Dynamic viscosity:</b>   | Not available.   |
| <b>Kinematic viscosity:</b>                                       | > 20.5 mm <sup>2</sup> /s  |
| <b>Particle characteristics:</b>                                  | Not applicable, Product is a liquid  |
| <b>Decomposition temperature:</b>                                 | Not available.   |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.   |
| <b>Hazardous reactions:</b>              | None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials. |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.  |
| <b>Incompatible materials:</b>           | Strong oxidizing agents.   |
| <b>Reactivity:</b>                       | Not available.   |
| <b>Conditions to avoid:</b>              | Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.           |

## 11. TOXICOLOGICAL INFORMATION

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Likely routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-----------------------------------|-----------------------------------|

### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system.  
**Skin contact:** May cause allergic skin reaction. Causes skin irritation.  
**Eye contact:** Causes serious eye irritation.  
**Ingestion:** May cause gastrointestinal tract irritation if swallowed. Not expected under normal conditions of use.

| Hazardous Component(s)  | LD50s and LC50s  |
|---|--|
| Polyglycol dioctanoate  | None   |
| Methacrylic acid, isobutyl ester, polymer with butyl methacrylate | None   |
| Cumene hydroperoxide  | None   |
| isobutyl methacrylate   | Oral LD50 (Mouse) = 11,990 mg/kg   |
| n-butyl methacrylate  | Oral LD50 (Mouse) = 15.8 g/kg<br>Oral LD50 (Rat) = 22,600 mg/kg<br>Oral LD50 (Rat) = 16.0 g/kg<br>Oral LD50 (Mouse) = 12,900 mg/kg<br>Dermal LD50 (Rabbit) = 11,300 mg/kg<br>Inhalation LC50 (Rat, 4 h) = 4910 ppm |

| Hazardous Component(s)  | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects            |
|---|--------------------------|------------------------|-----------------------------------|
| Polyglycol dioctanoate  | Irritant                 |                        |                                   |
| Methacrylic acid, isobutyl ester, polymer with butyl methacrylate | Irritant                 |                        |                                   |
| Cumene hydroperoxide  | Corrosive<br>Irritant    | Allergen               | Central nervous system<br>Mutagen |
| isobutyl methacrylate   | Irritant                 | Allergen               |                                   |
| n-butyl methacrylate  | Irritant                 | Allergen               |                                   |

| Hazardous Component(s)  | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------|-----------------|--|
| Polyglycol dioctanoate  | No             | No              | No                                       |
| Methacrylic acid, isobutyl ester, polymer with butyl methacrylate | No             | No              | No                                       |
| Cumene hydroperoxide  | No             | No              | No                                       |
| isobutyl methacrylate   | No             | No              | No                                       |
| n-butyl methacrylate  | No             | Group 2B        | No                                       |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**15. REGULATORY INFORMATION**

**Canada Regulatory Information**

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections: 9**

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 05/14/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.