



Revision Number: 006.1

Issue date: 04/09/2025

1. IDENTIFICATION

Product name:	LOCTITE PC 9660 TEMPORARY COATING known as Maxi-Coat Heavy Duty Rustproof	IDH number:	209752
Product type/Recommended use:	Coating	Item number:	51213
Restriction of Use:	None identified	Region:	Canada
Company address:	Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3	Contact information:	Telephone: +1 (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H226 - FLAMMABLE LIQUID AND VAPOUR.
H304 - MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
H315 - CAUSES SKIN IRRITATION.
H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention:

- P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking.
- P233 - Keep container tightly closed.
- P240 - Ground and bond container and receiving equipment.
- P241 - Use explosion-proof equipment.
- P242 - Use non-sparking tools.
- P243 - Take action to prevent static discharges.
- P264 - Wash affected area thoroughly after handling.
- P280 - Wear protective gloves, clothing, eye and face protection.

IDH number: 209752

Product name: LOCTITE PC 9660 TEMPORARY COATING known as Maxi-Coat Heavy Duty Rustproof

Response: P301+P310 - IF SWALLOWED: Immediately call a physician or poison control center.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical attention.
P337+P313 - If eye irritation persists: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Distillates (petroleum), hydrotreated light	64742-47-8	60 - 80
Sulfonic acids, petroleum, sodium salts	68608-26-4	5 - 10
2-Butoxyethanol	111-76-2	5 - 10

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

Most important symptoms and effects (acute and delayed): The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.

Indication of any immediate medical attention / special treatment needed: Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Improper extinguishing agents: Not available.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Cartridge respirators do not provide adequate protection for fire fighters or exotherm mitigation.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Water or foam may cause frothing. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of silicon. Aldehydes. Hydrocarbons. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Do not reuse container. Mineral may accumulate static charges which may cause an electrical spark.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated light	100 ppm TWA	500 ppm (2,900 mg/m ³) PEL	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m ³) PEL (SKIN)	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Amber
Odor:	Of hydrocarbons
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	> 2 mm hg
Boiling point/range:	Not available.
Melting point/ range:	-17.8 °C (0°F)
Density/Relative density:	0.87 - 0.91
Relative vapor density:	Heavier than air.
Flash point:	49 °C (120.2 °F) Cleveland closed cup
Flammable/Explosive limits - lower:	0.7 %
Flammable/Explosive limits - upper:	5 %
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	< 1
Solubility:	Insoluble Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	40 %; 349 g/l
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Not available.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of silicon. Aldehydes. Hydrocarbons. Toxic fumes. Irritating vapors.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact: Causes skin irritation.
Eye contact: Causes serious eye irritation.
Ingestion: May be harmful or fatal if swallowed. May cause an aspiration hazard if swallowed.

Hazardous Component(s)	LD50s and LC50s
Distillates (petroleum), hydrotreated light	Inhalation LC50 (Rat, 4 h) = > 7,630 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,610 mg/m3
Sulfonic acids, petroleum, sodium salts	Inhalation LC50 (Rat, 4 h) = > 1.9 mg/l
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg Inhalation LC50 (Rat, 4 h) = 523 ppm Inhalation LC50 (Rat, 4 h) = 545 ppm

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Distillates (petroleum), hydrotreated light	Irritant		Lung
Sulfonic acids, petroleum, sodium salts			
2-Butoxyethanol	Irritant		Blood Central nervous system Kidney Liver

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated light	No	No	No
Sulfonic acids, petroleum, sodium salts	No	No	No
2-Butoxyethanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: PAINT
Hazard class or division: 3
Identification number: UN 1263
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Paint
Hazard class or division: 3
Identification number: UN 1263
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: PAINT (Stoddard Solvent)
Hazard class or division: 3
Identification number: UN 1263
Packing group: III
Marine pollutant: Stoddard Solvent

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 8,9,11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 04/09/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.