



Revision Number: 007.2

Issue date: 10/16/2025

1. IDENTIFICATION

Product name: LOCTITE SF 768 CLEAN UP SOLVENT known as LOCTITE® X-NMS CLEAN UP SOLVEN
Product type/Recommended use: Solvent
Restriction of Use: None identified
Company address: Henkel Canada Corporation
 Meadowpine Boulevard 2515
 Mississauga, Ontario L5N 6C3

IDH number: 235018
Item number: 76820
Region: Canada
Contact information:
 Telephone: +1 (905) 814-6511
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: H226 - FLAMMABLE LIQUID AND VAPOUR.
 H302 - HARMFUL IF SWALLOWED.
 H351 - SUSPECTED OF CAUSING CANCER.
 H361 - SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
 H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
ACUTE TOXICITY ORAL	4
CARCINOGENICITY	2
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking.
 P233 - Keep container tightly closed.
 P240 - Ground and bond container and receiving equipment.

IDH number: 235018

Product name: LOCTITE SF 768 CLEAN UP SOLVENT known as LOCTITE® X-NMS CLEAN UP SOLVEN

Response: P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash affected area thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves, clothing, eye and face protection.
P301+P312+P330 - IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.
P308+P313 - IF exposed or concerned: Get medical attention.
P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: P403+P235 - Store in a well-ventilated place. Keep cool.

Disposal: P405 - Store locked up.
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
nitromethane	75-52-5	80 - 100
Toluene	108-88-3	5 - 10

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Drink 1-2 glasses of water, seek medical advice. Never give anything by mouth to an unconscious person.

Most important symptoms and effects (acute and delayed): The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.

Indication of any immediate medical attention / special treatment needed: Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Water spray mist or foam.

Improper extinguishing agents: Not available.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed container until ready for disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.

Storage: For safe storage, store at or below < 90 °F (< 32.2 °C) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Remove all sources of ignition. Ground and bond metal containers for liquid transfer to avoid static sparks.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
nitromethane	20 ppm TWA	100 ppm (250 mg/m ³) PEL	None	None
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling 500 ppm MAX. CONC 10 minutes	None	None

Engineering controls: Ensure adequate ventilation. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Respiratory protection: Use an organic vapor respirator for concentrations exceeding the Occupational Exposure Limit. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Clear
Odor:	Mild
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	25 mm hg (20 °C (68°F))
Boiling point/range:	111 °C (231.8 °F) Approximately
Melting point/ range:	Not available.
Density/Relative density:	1.1
Relative vapor density:	2.1 (Air = 1)
Flash point:	82.4 °F (28°C) ASTM D3278 Setaflash Closed Cup
Flammable/Explosive limits - lower:	7.3 %
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	6 Approximately, (Ether = 1)
Solubility:	Slight Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	100 %; 1,100 g/l EPA Method 24
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen.
Incompatible materials:	Amines. Alkalis. Acids. Reducing agents. Metal oxides. Combustible materials.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.
Skin contact: May cause skin irritation.
Eye contact: May cause irritation.
Ingestion: Harmful or fatal if swallowed.

Hazardous Component(s)	LD50s and LC50s
nitromethane	Oral LD50 (Rat) = 940 mg/kg Oral LD50 (Mouse) = 950 mg/kg Dermal LD50 (Rabbit) = > 2,000 mg/kg
Toluene	Oral LD50 (Rat) = 2.6 g/kg Dermal LD50 (Rabbit) = 12,124 mg/kg Inhalation LC50 (Rat, 4 h) = 12.5 - 28.8 mg/l Inhalation LC50 (Rat, 4 h) = 25.7 mg/l Inhalation LC50 (Rat, 4 h) = 28.1 mg/l Inhalation LC50 (Rat, 4 h) = 30 mg/l

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
nitromethane	Irritant		Blood Bone Marrow Kidney Liver Nervous System Reproductive Some evidence of carcinogenicity
Toluene	Irritant		Behavioral Cardiac Central nervous system Developmental Ear

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
nitromethane	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Toluene	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: NITROMETHANE solution
Hazard class or division: 3
Identification number: UN 1261
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Nitromethane solution
Hazard class or division: 3
Identification number: UN 1261
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: NITROMETHANE solution
Hazard class or division: 3
Identification number: UN 1261
Packing group: II

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 10/16/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.