



Revision Number: 005.1

Issue date: 11/10/2025

**1. IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE LB 8036 ANTI-SIEZE, WHITE</b>	<b>IDH number:</b>	302678
	<b>known as White Hi-Temp Anti-Seize</b>		
<b>Product type/</b>	Lubricant	<b>Item number:</b>	34518
<b>Recommended use:</b>			
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	Canada
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Canada Corporation	Telephone: +1 (905) 814-6511		
Meadowpine Boulevard 2515	MEDICAL EMERGENCY Phone: Poison Control Center		
Mississauga, Ontario L5N 6C3	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	MEDICAL EMERGENCY Phone: Poison Control Center		
	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** H315 - CAUSES SKIN IRRITATION.  
H318 - CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

**PICTOGRAM(S)**



**Precautionary Statements**

<b>Prevention:</b>	P264 - Wash affected area thoroughly after handling. P280 - Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical attention. P362+P364 - Take off contaminated clothing and wash it before reuse.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

**Other hazards** Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
White mineral oil (petroleum)	8042-47-5	30 - 60
White mineral oil~		10 - 30
Calcium oxide	1305-78-8	5 - 10
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	68411-54-1	5 - 10
Calcium fluoride	7789-75-5	5 - 10
Mica	12001-26-2	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Quartz (SiO <sub>2</sub> ), <1% respirable	14808-60-7	0.1 - 1
Kaolin	1332-58-7	0.1 - 1
Silica	7631-86-9	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>Skin contact:</b>	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	Get medical attention. Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis.
<b>Most important symptoms and effects (acute and delayed):</b>	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
<b>Indication of any immediate medical attention / special treatment needed:</b>	Not available.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Improper extinguishing agents:</b>	Not available.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
<b>Unusual fire or explosion hazards:</b>	None

**Hazardous combustion products:**

Hydrogen sulfide. Oxides of carbon. Oxides of nitrogen. Oxides of phosphorus. Oxides of zinc.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.

**Storage:**

Keep in a cool, well ventilated area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
White mineral oil (petroleum)	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 PEL Mist.	None	None
White mineral oil~	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	1 mg/m3 TWA Respirable fraction.	None	None	None
Calcium fluoride	2.5 mg/m3 TWA (as F)	2.5 mg/m3 PEL (as F) 2.5 mg/m3 TWA Dust.	None	None
Mica	0.1 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable 0.1 mg/m3 TWA Respirable	None	None

**Engineering controls:**

General room ventilation is usually adequate. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:**

Observe OSHA regulations for respirator use (29 CFR 1910.134). Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Solid, Paste
<b>Color:</b>	Off white
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Density/Relative density:</b>	1.116

<b>Relative vapor density:</b>	Not available.
<b>Flash point:</b>	Not applicable
<b>Flammable/Explosive limits - lower:</b>	Not determined
<b>Flammable/Explosive limits - upper:</b>	Not determined
<b>Autoignition temperature:</b>	Not determined
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not determined
<b>Solubility:</b>	Insoluble Water
<b>Partition coefficient n-octanol/water (logarithmic value):</b>	Not determined
<b>VOC content:</b>	0.4 %; 4.7 g/l
<b>Dynamic viscosity:</b>	Not available.
<b>Kinematic viscosity:</b>	Not available.
<b>Particle characteristics:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Hydrocarbons. Oxides of nitrogen. Oxides of phosphorus. Oxides of zinc. Hydrogen sulfide.
<b>Incompatible materials:</b>	Oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Prolonged exposure to heat.

## 11. TOXICOLOGICAL INFORMATION

<b>Likely routes of exposure:</b>	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

**Potential Health Effects/Symptoms**

**Inhalation:** This product has low volatility and is not expected to cause respiratory tract irritation during normal conditions of use. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

**Skin contact:** Causes skin irritation.

**Eye contact:** Causes serious eye damage.

**Ingestion:** Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
White mineral oil (petroleum)	Inhalation LC50 (Rat, 4 h) = > 5 mg/l
White mineral oil~	None
Calcium oxide	Inhalation LC50 (Rat, 4 h) = 40 mg/m3 Inhalation LC50 (Rat, 4 h) = 160 mg/m3
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	None
Calcium fluoride	Oral LD50 (Rat) = 4,250 mg/kg Inhalation LC50 (Rat, 4 h) = > 5,070 mg/m3
Mica	None
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l
Quartz (SiO2), <1% respirable	None
Kaolin	Oral LD50 (Rat) = > 5,000 mg/kg Dermal LD50 (Rat) = > 5,000 mg/kg
Silica	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
White mineral oil (petroleum)	Irritant		
White mineral oil~	Irritant		
Calcium oxide	Irritant Corrosive		Eyes
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid			
Calcium fluoride			Teeth Muscle Respiratory
Mica			Lung
Titanium dioxide	Irritant		Respiratory Some evidence of carcinogenicity
Quartz (SiO2), <1% respirable			Immune system Lung Some evidence of carcinogenicity
Kaolin	Nuisance dust		
Silica	Nuisance dust		

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
White mineral oil (petroleum)	No	No	No
White mineral oil~	No	No	No
Calcium oxide	No	No	No
Aluminum, tri-m-oxotris(2-propanolato)tri-, cyclo, reaction products with benzoic acid and stearic acid	No	No	No

Calcium fluoride	No	No	No
Mica	No	No	No
Titanium dioxide	No	Group 2B	No
Quartz (SiO <sub>2</sub> ), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes
Kaolin	No	No	No
Silica	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3, 4, 8, 11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 11/10/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.