



Revision Number: 006.1

Issue date: 08/22/2025

**1. IDENTIFICATION**

|                            |  |                             |   |
|----------------------------|--|-----------------------------|---|
| <b>Product name:</b>       | <b>LOCTITE SF F720 BL known as Color Guard® Blue</b>                                   | <b>IDH number:</b>          | 338128  |
| <b>Product type/</b>       | Coating  | <b>Item number:</b>         | 34983   |
| <b>Recommended use:</b>    |  | <b>Region:</b>              | Canada  |
| <b>Restriction of Use:</b> | None identified  | <b>Contact information:</b> |   |
| <b>Company address:</b>    | Henkel Canada Corporation<br>Meadowpine Boulevard 2515<br>Mississauga, Ontario L5N 6C3 | Telephone:                  | +1 (905) 814-6511   |
|                            |  | MEDICAL EMERGENCY Phone:    | Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711 |
|                            |  | TRANSPORT EMERGENCY Phone:  | CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887              |
|                            |  | MEDICAL EMERGENCY Phone:    | Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711 |
|                            |  | TRANSPORT EMERGENCY Phone:  | CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887              |
|                            |  | Internet:                   | www.henkelna.com  |

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** H225 - HIGHLY FLAMMABLE LIQUID AND VAPOUR.  
H304 - MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
H315 - CAUSES SKIN IRRITATION.  
H319 - CAUSES SERIOUS EYE IRRITATION.  
H336 - MAY CAUSE DROWSINESS OR DIZZINESS.  
H351 - SUSPECTED OF CAUSING CANCER.  
H361 - SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.  
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| FLAMMABLE LIQUID                                   | 2               |
| SKIN IRRITATION                                    | 2               |
| EYE IRRITATION                                     | 2A              |
| CARCINOGENICITY                                    | 2               |
| REPRODUCTIVE TOXICITY                              | 2               |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE   | 3               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |
| ASPIRATION HAZARD                                  | 1               |

**PICTOGRAM(S)**



**Precautionary Statements**

IDH number: 338128

Product name: LOCTITE SF F720 BL known as Color Guard® Blue

|                    |   |
|--------------------|---|
| <b>Prevention:</b> | <p>P201 - Obtain special instructions before use.</p> <p>P202 - Do not handle until all safety precautions have been read and understood.</p> <p>P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground and bond container and receiving equipment.</p> <p>P241 - Use explosion-proof equipment.</p> <p>P242 - Use non-sparking tools.</p> <p>P243 - Take action to prevent static discharges.</p> <p>P260 - Do not breathe vapors, mist, or spray.</p> <p>P264 - Wash affected area thoroughly after handling.</p> <p>P271 - Use only outdoors or in a well-ventilated area.</p> <p>P280 - Wear protective gloves, clothing, eye and face protection.</p>   |
| <b>Response:</b>   | <p>P301+P310 - IF SWALLOWED: Immediately call a physician or poison control center.</p> <p>P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.</p> <p>P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 - IF exposed or concerned: Get medical attention.</p> <p>P331 - Do NOT induce vomiting.</p> <p>P332+P313 - If skin irritation occurs: Get medical attention.</p> <p>P337+P313 - If eye irritation persists: Get medical attention.</p> <p>P362+P364 - Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.</p> |
| <b>Storage:</b>    | <p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 - Store in a well-ventilated place. Keep cool.</p> <p>P405 - Store locked up.</p>  |
| <b>Disposal:</b>   | <p>P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.</p>   |

**Other hazards** Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)   | CAS Number | Weight %* |
|--|------------|-----------|
| Distillates (petroleum), light distillate hydrotreating process, low-boiling | 68410-97-9 | 10 - 30   |
| Solvent naphtha (petroleum), light aliph., <0.1% benzene                     | 64742-89-8 | 10 - 30   |
| Naphtha (petroleum), hydrotreated light                                      | 64742-49-0 | 10 - 30   |
| Xylenes  | 1330-20-7  | 10 - 30   |
| n-Hexane   | 110-54-3   | 10 - 30   |
| acetone  | 67-64-1    | 10 - 30   |
| Ethylbenzene   | 100-41-4   | 5 - 10    |
| Octane   | 111-65-9   | 1 - 5     |
| n-Heptane  | 142-82-5   | 1 - 5     |
| Titanium dioxide   | 13463-67-7 | 1 - 5     |
| Cumene   | 98-82-8    | 1 - 5     |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

### First Aid Measures by likely routes of exposure

|  |  |
|--|--|
| <b>Inhalation:</b>   | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.                                      |
| <b>Skin contact:</b>   | Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Wash clothing before reuse. If symptoms develop and persist, get medical attention. |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.  |
| <b>Ingestion:</b>  | Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.  |
| <b>Most important symptoms and effects (acute and delayed):</b>                  | The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.   |
| <b>Indication of any immediate medical attention / special treatment needed:</b> | Not available.   |

## 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Foam, dry chemical or carbon dioxide.  |
| <b>Improper extinguishing agents:</b>     | Not available.   |
| <b>Special firefighting procedures:</b>   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.                         |
| <b>Unusual fire or explosion hazards:</b> | Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Toxic and irritating vapors.   |

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |   |
|-----------------------------------|---|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.   |
| <b>Clean-up methods:</b>          | Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed container until ready for disposal. |

## 7. HANDLING AND STORAGE

|                  |   |
|------------------|---|
| <b>Handling:</b> | Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Keep away from heat, spark and flame.  |
| <b>Storage:</b>  | For safe storage, store at or below 48 °C (118.4 °F)<br>Keep in a cool, well ventilated area away from heat, sparks and open flame.<br>Keep container tightly closed until ready for use. |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)   | ACGIH TLV  | OSHA PEL   | AIHA WEEL | OTHER |
|--|--|--|-----------|-------|
| Distillates (petroleum), light distillate hydrotreating process, low-boiling | 5 mg/m <sup>3</sup> TWA<br>Inhalable fraction.   | 5 mg/m <sup>3</sup> PEL Mist.  | None      | None  |
| Solvent naphtha (petroleum), light aliph., <0.1% benzene                     | (SKIN)<br>100 ppm TWA  | 100 ppm (400 mg/m <sup>3</sup> ) PEL   | None      | None  |
| Naphtha (petroleum), hydrotreated light                                      | 100 ppm TWA<br>(SKIN)  | 100 ppm (400 mg/m <sup>3</sup> ) PEL   | None      | None  |
| Xylenes  | 20 ppm TWA   | 100 ppm (435 mg/m <sup>3</sup> ) PEL   | None      | None  |
| n-Hexane   | 50 ppm TWA<br>(SKIN)   | 500 ppm (1,800 mg/m <sup>3</sup> ) PEL   | None      | None  |
| acetone  | 250 ppm TWA<br>500 ppm STEL  | 1,000 ppm (2,400 mg/m <sup>3</sup> ) PEL   | None      | None  |
| Ethylbenzene   | 20 ppm TWA   | 100 ppm (435 mg/m <sup>3</sup> ) PEL   | None      | None  |
| Octane   | 300 ppm TWA  | 500 ppm (2,350 mg/m <sup>3</sup> ) PEL   | None      | None  |
| n-Heptane  | 200 ppm TWA<br>400 ppm STEL  | 500 ppm (2,000 mg/m <sup>3</sup> ) PEL   | None      | None  |
| Titanium dioxide   | 0.2 mg/m <sup>3</sup> TWA<br>Respirable<br>nanoscale particles<br>2.5 mg/m <sup>3</sup> TWA<br>Respirable<br>finescale particles | 15 mg/m <sup>3</sup> PEL<br>Total dust.<br>15 MPPCF TWA<br>Respirable fraction.<br>15 mg/m <sup>3</sup> TWA<br>Total dust.<br>50 MPPCF TWA<br>Total dust.<br>5 mg/m <sup>3</sup> TWA<br>Respirable fraction. | None      | None  |
| Cumene   | 5 ppm TWA  | 50 ppm (245 mg/m <sup>3</sup> ) PEL<br>(SKIN)  | None      | None  |

**Engineering controls:**

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Chemical resistant, impermeable gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |                                |
|--|--------------------------------|
| <b>Physical state:</b>                     | Liquid                         |
| <b>Color:</b>                              | Blue                           |
| <b>Odor:</b>                               | Hydrocarbons                   |
| <b>Odor threshold:</b>                     | Not available.                 |
| <b>pH:</b>                                 | Not available.                 |
| <b>Vapor pressure:</b>                     | 185 mm hg (20 °C (68°F))       |
| <b>Boiling point/range:</b>                | 56 - 141 °C (132.8 - 285.8 °F) |
| <b>Melting point/ range:</b>               | Not available.                 |
| <b>Density/Relative density:</b>           | 0.79 - 0.83                    |
| <b>Relative vapor density:</b>             | > 1 Heavier than air           |
| <b>Flash point:</b>                        | -23 °C (-9.4 °F)               |
| <b>Flammable/Explosive limits - lower:</b> | 0.9 %                          |
| <b>Flammable/Explosive limits - upper:</b> | 12.8 %                         |
| <b>Autoignition temperature:</b>           | Not available.                 |

|   |                                   |
|---|-----------------------------------|
| <b>Flammability:</b>  | Not applicable                    |
| <b>Evaporation rate:</b>  | Greater than butyl acetate.       |
| <b>Solubility:</b>  | Insoluble Water                   |
| <b>Partition coefficient n-octanol/water (logarithmic value):</b> | Not available.                    |
| <b>VOC content:</b>   | 70.01 %; 559.27 g/l EPA Method 24 |
| <b>Dynamic viscosity:</b>   | Not available.                    |
| <b>Kinematic viscosity:</b>                                       | Not available.                    |
| <b>Particle characteristics:</b>                                  | Not available.                    |
| <b>Decomposition temperature:</b>                                 | Not available.                    |

## 10. STABILITY AND REACTIVITY

|  |   |
|--|---|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.  |
| <b>Hazardous reactions:</b>              | Will not occur.   |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Irritating organic vapours.   |
| <b>Incompatible materials:</b>           | Strong acids and strong bases. Strong oxidizing agents. Amines. Alkali metals. Halogenated compounds. |
| <b>Reactivity:</b>                       | Not available.  |
| <b>Conditions to avoid:</b>              | Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.           |

## 11. TOXICOLOGICAL INFORMATION

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Likely routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-----------------------------------|-----------------------------------|

**Potential Health Effects/Symptoms**

**Inhalation:** Vapors may cause headaches, nausea, dizziness and respiratory tract irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged exposure to solvents may cause adverse effects to the liver, urinary, and reproductive systems.

**Skin contact:** Causes skin irritation.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

| Hazardous Component(s)   | LD50s and LC50s   |
|--|---|
| Distillates (petroleum), light distillate hydrotreating process, low-boiling | Inhalation LC50 (Rat, 4 h) = > 4,970 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 7,970 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,050 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,220 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 4.96 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5,000 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,740 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 4,980 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,170 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5.1 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5,250 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,080 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,280 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,020 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,040 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 4,420 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 8,530 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,240 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,100 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,000 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,300 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 7,300 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5.36 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 7,630 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,610 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,470 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,300 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5.07 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5,260 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,000 mg/m3<br>Inhalation LC50 (Rat, 4 h) = >= 5,060 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,830 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,160 mg/m3<br>Inhalation LC50 (Rat, 4 h) = > 5,200 mg/m3 |
| Solvent naphtha (petroleum), light aliph., <0.1% benzene                     | None  |

|   |  |
|---|--|
| Naphtha (petroleum), hydrotreated light | <p>Inhalation LC50 (Rat, 4 h) = 13700 ppm<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,100 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,280 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,000 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,830 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = 30 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,080 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,160 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 4,970 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,170 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 4,420 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,050 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,020 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,220 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,000 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,200 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,240 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 7,970 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = 43,767 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 8,530 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,260 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 7,300 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,300 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5.07 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5.36 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,300 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,470 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,610 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 7,630 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,000 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 4,980 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = 25.7 mg/l<br/> Inhalation LC50 (Rat, 4 h) = 28.1 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,740 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,040 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt;= 5,060 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5,250 mg/m3<br/> Inhalation LC50 (Rat, 4 h) = &gt; 5.1 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 4.96 mg/l</p> |
| Xylenes                                 | <p>Oral LD50 (Rat) = 6,670 mg/kg<br/> Oral LD50 (Rat) = 3,523 - 8,600 mg/kg<br/> Oral LD50 (Rat) = 4,300 mg/kg<br/> Dermal LD50 (Rabbit) = &gt; 43 g/kg<br/> Inhalation LC50 (Rat, 4 h) = 6580 ppm<br/> Inhalation LC50 (Rat, 4 h) = 6247 ppm<br/> Inhalation LC50 (Rat, 4 h) = 5922 ppm<br/> Inhalation LC50 (Rat, 4 h) = 6700 ppm<br/> Inhalation LC50 (Rat, 4 h) = 6350 ppm</p>   |
| n-Hexane                                | <p>Oral LD50 (Rat) = 28,710 mg/kg</p>  |
| acetone                                 | <p>Oral LD50 (Mouse) = 5.2 g/kg<br/> Oral LD50 (Mouse) = 3,000 mg/kg<br/> Oral LD50 (Rabbit) = 5,340 mg/kg<br/> Oral LD50 (Rat) = 5,800 mg/kg<br/> Oral LD50 (Rat) = 9,800 mg/kg<br/> Dermal LD50 (Rabbit) = 20,000 mg/kg<br/> Inhalation LC50 (Rat, 4 h) = 76 mg/l<br/> Inhalation LC50 (Rat, 4 h) = 50.1 mg/l</p>  |
| Ethylbenzene                            | <p>Oral LD50 (Rat) = 5.46 g/kg<br/> Oral LD50 (Rat) = 3,500 mg/kg<br/> Dermal LD50 (Rabbit) = 17,800 mg/kg<br/> Inhalation LC50 (Rat, 4 h) = 4000 ppm</p>  |
| Octane                                  | <p>Inhalation LC50 (Rat, 4 h) = &gt; 24.88 mg/l</p>  |
| n-Heptane                               | <p>Inhalation LC50 (Rat, 4 h) = &gt; 73.5 mg/l<br/> Inhalation LC50 (Rat, 4 h) = &gt; 29.29 mg/l</p>   |

|                  |  |
|------------------|--|
| Titanium dioxide | Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l |
| Cumene           | Oral LD50 (Rat) = 2.91 g/kg<br>Oral LD50 (Rat) = 1,400 mg/kg   |

| Hazardous Component(s)   | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects                                  |
|--|--------------------------|------------------------|---|
| Distillates (petroleum), light distillate hydrotreating process, low-boiling |                          |                        |   |
| Solvent naphtha (petroleum), light aliph., <0.1% benzene                     | Irritant                 |                        |   |
| Naphtha (petroleum), hydrotreated light                                      | Irritant                 |                        | Central nervous system<br>Kidney<br>Lung                |
| Xylenes  | Irritant                 |                        | Cardiac<br>Central nervous system<br>Kidney<br>Liver    |
| n-Hexane   | Irritant                 |                        | Developmental<br>Lung<br>Nervous System<br>Reproductive |
| acetone  | Irritant                 |                        | Central nervous system                                  |
| Ethylbenzene   | Irritant                 |                        | Central nervous system                                  |
| Octane   | Irritant                 |                        | Central nervous system<br>Lung                          |
| n-Heptane  | Irritant                 |                        | Central nervous system                                  |
| Titanium dioxide   | Irritant                 |                        | Respiratory<br>Some evidence of carcinogenicity         |
| Cumene   | Irritant                 |                        | Central nervous system<br>Lung                          |

| Hazardous Component(s)   | NTP Carcinogen                                   | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|--|-----------------|--|
| Distillates (petroleum), light distillate hydrotreating process, low-boiling | No   | No              | No                                       |
| Solvent naphtha (petroleum), light aliph., <0.1% benzene                     | No   | No              | No                                       |
| Naphtha (petroleum), hydrotreated light                                      | No   | No              | No                                       |
| Xylenes  | No   | No              | No                                       |
| n-Hexane   | No   | No              | No                                       |
| acetone  | No   | No              | No                                       |
| Ethylbenzene   | No   | Group 2B        | No                                       |
| Octane   | No   | No              | No                                       |
| n-Heptane  | No   | No              | No                                       |
| Titanium dioxide   | No   | Group 2B        | No                                       |
| Cumene   | Reasonably Anticipated to be a Human Carcinogen. | Group 2B        | No                                       |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** COATING SOLUTION  
**Hazard class or division:** 3  
**Identification number:** UN 1139  
**Packing group:** II

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Coating solution  
**Hazard class or division:** 3  
**Identification number:** UN 1139  
**Packing group:** II

### Water Transportation (IMO/IMDG)

**Proper shipping name:** COATING SOLUTION (n-Heptane, Octane)  
**Hazard class or division:** 3  
**Identification number:** UN 1139  
**Packing group:** II  
**Marine pollutant:** n-Heptane, Octane

## 15. REGULATORY INFORMATION

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections: 9**

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 08/22/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.