



Revision Number: 004.0

Issue date: 06/19/2025

1. IDENTIFICATION

Product name:	TECHNOMELT 1942	IDH number:	416035
	YSHOT 35 LB CT		
Product type/	Assembly adhesives	Item number:	83277
Recommended use:			
Restriction of Use:	None identified	Region:	Canada
Company address:		Contact information:	
Henkel Canada Corporation		Telephone: +1 (905) 814-6511	
Meadowpine Boulevard 2515		MEDICAL EMERGENCY Phone: Poison Control Center	
Mississauga, Ontario L5N 6C3		1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone: CHEMTREC	
		1-800-424-9300 (toll free) or 1-703-527-3887	
		MEDICAL EMERGENCY Phone: Poison Control Center	
		1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone: CHEMTREC	
		1-800-424-9300 (toll free) or 1-703-527-3887	
		Internet: www.henkelna.com	

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.
 VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND
 RESPIRATORY TRACT IRRITATION.
 STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR
 FLAMMABLE VAPORS MAY CAUSE IGNITION.
 H317 MAY CAUSE AN ALLERGIC SKIN REACTION.
 H334 MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
 DIFFICULTIES IF INHALED.
 H351 SUSPECTED OF CAUSING CANCER.

HAZARD CLASS	HAZARD CATEGORY
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
CARCINOGENICITY	2

PICTOGRAM(S)



Precautionary Statements

Prevention:

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P261 - Avoid breathing dust or fumes.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P280 - Wear protective gloves, clothing, eye and face protection.
- P284 - [In case of inadequate ventilation] wear respiratory protection.

IDH number: 416035

Product name: TECHNOMELT 1942

YSHOT 35 LB CT

Response: P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - IF exposed or concerned: Get medical attention.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P342+P311 - If experiencing respiratory symptoms: Call a poison center or physician.
P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
rosin	8050-09-7	10 - 30
Paraffin waxes and Hydrocarbon waxes	8002-74-2	1 - 5
Vinyl acetate	108-05-4	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation: Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn.

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.

Ingestion: Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.

Most important symptoms and effects (acute and delayed): The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.

Indication of any immediate medical attention / special treatment needed: Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing measures appropriate to local circumstances and the surrounding environment. Water spray (fog), foam, dry chemical or carbon dioxide.

Improper extinguishing agents: Not available.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Acrid smoke and fumes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system.

Clean-up methods: Sweep up spilled material. Avoid creating dust. Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Do not place wet or damp solid into melt tank. Follow suggested application temperature. Always be careful around molten material. Avoid skin contact with molten resins. Do not wear contact lenses. Avoid dust formation.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
rosin	0.001 mg/m ³ TWA (as total Resin Acids) Inhalable fraction. (Dermal sensitization) (Respiratory sensitization)	None	None	None
Paraffin waxes and Hydrocarbon waxes	2 mg/m ³ TWA Fume.	None	None	None
Vinyl acetate	10 ppm TWA 15 ppm STEL	None	None	None

Engineering controls: Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Heat only in areas with appropriate exhaust ventilation.

Respiratory protection: Respirator with combination filter for vapor/particulate. In case of insufficient ventilation wear suitable respiratory equipment.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Yellow, Translucent
Odor:	Slight, Resinous
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not applicable
Boiling point/range:	Not available.
Melting point/ range:	110.2 °C (230.4 °F)
Density/Relative density:	0.95
Relative vapor density:	Not available.
Flash point:	Product is a solid
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not applicable
Solubility:	Insoluble Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	0 %; 0 g/l
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Acrid smoke and fumes.
Incompatible materials:	Avoid heating above 400°F.
Reactivity:	Not available.
Conditions to avoid:	Prolonged heating at temperatures above 200 °C.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Fumes may be irritating and may cause an allergic respiratory reaction. Dusts from solid adhesive may cause irritation.

Skin contact: Causes skin irritation. Molten adhesive may cause severe burns. May cause allergic skin reaction.

Eye contact: Molten adhesive in eyes will cause severe and permanent damage. Causes serious eye irritation. Can cause mechanical irritation if dusts are generated.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s
rosin	None
Paraffin waxes and Hydrocarbon waxes	None
Vinyl acetate	Oral LD50 (Rat) = 2,920 mg/kg Oral LD50 (Mouse) = 1,613 mg/kg Dermal LD50 (Rabbit) = 2,335 mg/kg Inhalation LC50 (Rat, 4 h) = 4490 ppm

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
rosin	Irritant	Allergen	Respiratory
Paraffin waxes and Hydrocarbon waxes	Irritant		
Vinyl acetate	Irritant		Central nervous system Mutagen Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
rosin	No	No	No
Paraffin waxes and Hydrocarbon waxes	No	No	No
Vinyl acetate	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Exceptions: None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format. 1-16

Prepared by: Regulatory Affairs

Issue date: 06/19/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.