



Revision Number: 004.1

Issue date: 09/18/2025

**1. IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE FREKOTE LIFFT-I known as FREKOTE LIFFT-1 5 GALLON PAIL</b>	<b>IDH number:</b>	420456
<b>Product type/ Recommended use:</b>	Release agent	<b>Item number:</b>	83554
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	Canada
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Canada Corporation	Telephone: +1 (905) 814-6511		
Meadowpine Boulevard 2515	MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711		
Mississauga, Ontario L5N 6C3	TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887		
	MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** H226 - FLAMMABLE LIQUID AND VAPOUR.  
 H304 - MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
 H315 - CAUSES SKIN IRRITATION.  
 H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.  
 H319 - CAUSES SERIOUS EYE IRRITATION.  
 H336 - MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

**PICTOGRAM(S)**



**Precautionary Statements**

**Prevention:** P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground and bond container and receiving equipment.  
 P241 - Use explosion-proof equipment.  
 P242 - Use non-sparking tools.  
 P243 - Take action to prevent static discharges.

IDH number: 420456

Product name: LOCTITE FREKOTE LIFFT-I known as FREKOTE LIFFT-1 5 GALLON PAIL

**Response:** P261 - Avoid breathing mist/vapours.  
P264 - Wash affected area thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P280 - Wear protective gloves, clothing, eye and face protection.  
P301+P310 - IF SWALLOWED: Immediately call a physician or poison control center.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.  
P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical attention.  
P337+P313 - If eye irritation persists: Get medical attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

**Storage:** P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.

**Disposal:** P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Other hazards** Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Alkanes, C7-10-iso-	90622-56-3	80 - 100
Trimethoxy(methyl)silane	1185-55-3	0.1 - 1
Xylenes	1330-20-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

<b>Ingestion:</b>	Keep individual calm. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Never give anything by mouth to an unconscious person. Get immediate medical attention. If vomiting occurs, prevent aspiration by keeping the patient's head below the knees.
<b>Most important symptoms and effects (acute and delayed):</b>	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
<b>Indication of any immediate medical attention / special treatment needed:</b>	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.
<b>Improper extinguishing agents:</b>	Not available.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool. Keep personnel upwind of fire.
<b>Unusual fire or explosion hazards:</b>	Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of flammable liquids.
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Formaldehyde Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

## 6. ACCIDENTAL RELEASE MEASURES

**Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways. Advise authorities if product has entered or may enter sewers, water sources or extensive land areas. Prevent further leakage or spillage if safe to do so. This product is insoluble in water and will float on surface.
<b>Clean-up methods:</b>	Remove all sources of ignition. Ventilate area. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed metal container until ready for disposal. Keep upwind of the spilled material and isolate exposure. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. For operations where eye or face contact could occur, provide safety shower and eyewash fountain.
<b>Storage:</b>	For safe storage, store at or below 48.8 °C (119.8 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Trimethoxy(methyl)silane	None	None	10 ppm (55 mg/m3) TWA	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m3) PEL	None	None

<b>Engineering controls:</b>	Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product.
<b>Respiratory protection:</b>	Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
<b>Skin protection:</b>	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Colourless / Colorless
<b>Odor:</b>	Mild, Solvent
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	40 mm hg (20 °C (68°F)) Estimated
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Density/Relative density:</b>	0.720 Approximately
<b>Relative vapor density:</b>	Not available.
<b>Flash point:</b>	31 °C (87.8 °F) Tagliabue closed cup
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility:</b>	Negligible Water
<b>Partition coefficient n-octanol/water (logarithmic value):</b>	Not available.
<b>VOC content:</b>	92 %
<b>Dynamic viscosity:</b>	Not available.

**Kinematic viscosity:** Not available.  
**Particle characteristics:** Not available.  
**Decomposition temperature:** Not available.

## 10. STABILITY AND REACTIVITY

**Stability:** Risk of ignition. Stable under normal conditions of storage and use.

**Hazardous reactions:** Will not occur.

**Hazardous decomposition products:** Oxides of carbon. Oxides of silicon. Formaldehyde Hydrocarbons. Irritating organic vapours.

**Incompatible materials:** Strong oxidizing agents. Humid air. Water.

**Reactivity:** Not available.

**Conditions to avoid:** Avoid static discharge. Vapors may form explosive mixtures with air. Spray mist may be flammable at temperatures below the flash point. Keep away from open flames, hot surfaces and sources of ignition. Exposure to air or moisture over prolonged periods. Fire or intense heat may cause violent rupture of packages.

## 11. TOXICOLOGICAL INFORMATION

**Likely routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects/Symptoms**

**Inhalation:** Vapors and mists will irritate nose and throat and possibly eyes. High vapor concentrations (greater than approximately 1000 ppm) may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction. Solvent action can dry and defat the skin, causing the skin to crack, leading to dermatitis.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** This product may be fatal if it is swallowed. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.

Hazardous Component(s)	LD50s and LC50s
Alkanes, C7-10-iso-	None
Trimethoxy(methyl)silane	Inhalation LC50 (Rat, 4 h) = > 26000 ppm
Xylenes	Oral LD50 (Rat) = 6,670 mg/kg Oral LD50 (Rat) = 3,523 - 8,600 mg/kg Oral LD50 (Rat) = 4,300 mg/kg Dermal LD50 (Rabbit) = > 43 g/kg Inhalation LC50 (Rat, 4 h) = 6580 ppm Inhalation LC50 (Rat, 4 h) = 6247 ppm Inhalation LC50 (Rat, 4 h) = 5922 ppm Inhalation LC50 (Rat, 4 h) = 6700 ppm Inhalation LC50 (Rat, 4 h) = 6350 ppm
Ethylbenzene	Oral LD50 (Rat) = 5.46 g/kg Oral LD50 (Rat) = 3,500 mg/kg Dermal LD50 (Rabbit) = 17,800 mg/kg Inhalation LC50 (Rat, 4 h) = 4000 ppm

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Alkanes, C7-10-iso-	Irritant		Central nervous system Lung Cardiac
Trimethoxy(methyl)silane	Irritant	Allergen	
Xylenes	Irritant		Cardiac Central nervous system Kidney Liver
Ethylbenzene	Irritant		Central nervous system

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Alkanes, C7-10-iso-	No	No	No
Trimethoxy(methyl)silane	No	No	No
Xylenes	No	No	No
Ethylbenzene	No	Group 2B	No

**12. ECOLOGICAL INFORMATION**

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

#### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** RESIN SOLUTION  
**Hazard class or division:** 3  
**Identification number:** UN 1866  
**Packing group:** III

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Resin solution  
**Hazard class or division:** 3  
**Identification number:** UN 1866  
**Packing group:** III

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** RESIN SOLUTION (Isoalkane C7 - C10)  
**Hazard class or division:** 3  
**Identification number:** UN 1866  
**Packing group:** III  
**Marine pollutant:** Isoalkane C7 - C10

### 15. REGULATORY INFORMATION

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

### 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format. 3, 8, 11, 15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 09/18/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.