



Revision Number: 007.1

Issue date: 11/25/2025

1. IDENTIFICATION

| | | | |
|---------------------------------------|--|-----------------------------|--|
| Product name: | LOCTITE FREKOTE WOLO known as FREKOTE® WOLO™ MOLD RELEASE AG | IDH number: | 420480 |
| Product type/ Recommended use: | Release agent | Item number: | 83633 |
| Restriction of Use: | None identified | Region: | Canada |
| Company address: | Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3 | Contact information: | Telephone: +1 (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H225 - HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H304 - MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
H315 - CAUSES SKIN IRRITATION.
H336 - MAY CAUSE DROWSINESS OR DIZZINESS.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| FLAMMABLE LIQUID | 2 |
| SKIN IRRITATION | 2 |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3 |
| ASPIRATION HAZARD | 1 |

PICTOGRAM(S)



Precautionary Statements

Prevention:

- P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking.
- P233 - Keep container tightly closed.
- P240 - Ground and bond container and receiving equipment.
- P241 - Use explosion-proof equipment.
- P242 - Use non-sparking tools.
- P243 - Take action to prevent static discharges.
- P261 - Avoid breathing mist/vapours.
- P264 - Wash affected area thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.

IDH number: 420480

Product name: LOCTITE FREKOTE WOLO known as FREKOTE® WOLO™ MOLD RELEASE AG

Response: P280 - Wear protective gloves, clothing, eye and face protection.
P301+P310 - IF SWALLOWED: Immediately call a physician or poison control center.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.
P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Weight %* |
|--|--------------|-----------|
| Hydrocarbons, C7-C9, isoalkanes | 1174921-67-5 | 60 - 80 |
| Hydrocarbons, C10-C12, isoalkanes, <2% aromatics | 65072-03-9 | 30 - 60 |
| 2,2,4-trimethylpentane | 540-84-1 | 0.1 - 1 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse.

Eye contact: Check for and remove any contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get immediate medical attention.

Ingestion: Keep individual calm. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Never give anything by mouth to an unconscious person. If vomiting occurs, prevent aspiration by keeping the patient's head below the knees. Get immediate medical attention.

Most important symptoms and effects (acute and delayed): The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.

Indication of any immediate medical attention / special treatment needed: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet. |
| Improper extinguishing agents: | Not available. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Keep personnel upwind of fire. |
| Unusual fire or explosion hazards: | Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of flammable liquids. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. In case of fire, keep containers cool with water spray. |
| Hazardous combustion products: | Oxides of carbon. Hydrocarbons. Acrid smoke and fumes. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|--|
| Environmental precautions: | Do not allow product to enter sewer or waterways. Advise authorities if product has entered or may enter sewers, water sources or extensive land areas. Prevent further leakage or spillage if safe to do so. This product is insoluble in water and will float on surface. |
| Clean-up methods: | Remove all sources of ignition. Ventilate area. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed metal container until ready for disposal. Keep upwind of the spilled material and isolate exposure. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. |

7. HANDLING AND STORAGE

| | |
|------------------|--|
| Handling: | During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. For operations where eye or face contact could occur, provide safety shower and eyewash fountain. |
| Storage: | For safe storage, store between 5 °C (41°F) and 25 °C (77°F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|-----------|----------|-----------|-------|
| None | None | None | None | None |

| | |
|------------------------------|---|
| Engineering controls: | Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product. |
|------------------------------|---|

| | |
|--------------------------------|---|
| Respiratory protection: | Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists. |
| Eye/face protection: | Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available. |
| Skin protection: | Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Physical state: | Liquid |
| Color: | Colourless / Colorless |
| Odor: | Mild, Solvent |
| Odor threshold: | Not available. |
| pH: | Not applicable, Product is non-polar/aprotic. |
| Vapor pressure: | 12 mbar (20 °C (68°F)) |
| Boiling point/range: | > 112 °C (> 233.6 °F) |
| Melting point/ range: | Not applicable, Product is a liquid |
| Density/Relative density: | 0.725 |
| Relative vapor density: | 20 °C Heavier than air. |
| Flash point: | 6 °C (42.8 °F) Tagliabue closed cup |
| Flammable/Explosive limits - lower: | 0.6 % The product is not explosive. The formation of explosive vapor/air mixtures is possible. |
| Flammable/Explosive limits - upper: | 11.6 % The product is not explosive. The formation of explosive vapor/air mixtures is possible. |
| Autoignition temperature: | The substance or mixture is not classified as pyrophoric. |
| Flammability: | Flammable liquid |
| Evaporation rate: | Slower than ether. |
| Solubility: | Slight Water |
| Solubility: | Soluble other organic solvents |
| Partition coefficient n-octanol/water (logarithmic value): | Not available. |
| VOC content: | 99.39 %; 721 g/l |
| Dynamic viscosity: | Not available. |
| Kinematic viscosity: | 0.72 mm ² /s |
| Particle characteristics: | Not applicable, Product is a liquid |
| Decomposition temperature: | Not available. |

10. STABILITY AND REACTIVITY

| | |
|--|---|
| Stability: | Stable under normal conditions of storage and use. |
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | Oxides of carbon. Hydrocarbons. Acrid smoke and fumes. |
| Incompatible materials: | Strong oxidizing agents. Humid air. Water. |
| Reactivity: | Not available. |
| Conditions to avoid: | Avoid static discharge. Vapors may form explosive mixtures with air. Spray mist may be flammable at temperatures below the flash point. Keep away from open flames, hot surfaces and sources of ignition. Fire or intense heat may cause violent rupture of packages. |

11. TOXICOLOGICAL INFORMATION

| | |
|-----------------------------------|-----------------------------------|
| Likely routes of exposure: | Skin, Inhalation, Eyes, Ingestion |
|-----------------------------------|-----------------------------------|

Potential Health Effects/Symptoms

Inhalation: Vapors and mists will irritate nose and throat and possibly eyes. High vapor concentrations (greater than approximately 1000 ppm) may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

Skin contact: Causes skin irritation. May cause allergic skin reaction. Solvent action can dry and defat the skin, causing the skin to crack, leading to dermatitis.

Eye contact: May cause irritation.

Ingestion: This product may be fatal if it is swallowed. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.

| Hazardous Component(s) | LD50s and LC50s |
|--|---|
| Hydrocarbons, C7-C9, isoalkanes | None |
| Hydrocarbons, C10-C12, isoalkanes, <2% aromatics | None |
| 2,2,4-trimethylpentane | Inhalation LC50 (Rat, 4 h) = > 33.52 mg/l |

| Hazardous Component(s) | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects |
|--|--------------------------|------------------------|---|
| Hydrocarbons, C7-C9, isoalkanes | | | |
| Hydrocarbons, C10-C12, isoalkanes, <2% aromatics | | | |
| 2,2,4-trimethylpentane | Irritant | | Lung Central nervous system Liver Kidney |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Hydrocarbons, C7-C9, isoalkanes | No | No | No |
| Hydrocarbons, C10-C12, isoalkanes, <2% aromatics | No | No | No |
| 2,2,4-trimethylpentane | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: RESIN SOLUTION
Hazard class or division: 3
Identification number: UN 1866
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Resin solution
Hazard class or division: 3
Identification number: UN 1866
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: RESIN SOLUTION (Isoalkane C7 - C10)
Hazard class or division: 3
Identification number: UN 1866
Packing group: II
Marine pollutant: Isoalkane C7 - C10

15. REGULATORY INFORMATION**Canada Regulatory Information**

CEPA DSL/NDL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
This product contains one or more components with a Low Volume Exemption (LVE) in accordance with 40 CFR 723.50. Quantities may be limited.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3, 4, 8, 9, 11, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/25/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.