



Revision Number: 006.0

Issue date: 03/06/2025

1. IDENTIFICATION

Product name:	LOCTITE LB 8065 COPPER ANTI-SEIZE STICK known as C5-A® Copper Anti-Seize Stick	IDH number:	466863
Product type/Recommended use:	Lubricant	Item number:	37229
Restriction of Use:	None identified	Region:	Canada
Company address:	Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3	Contact information:	Telephone: +1 (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: H372 - CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

HAZARD CATEGORY

1

PICTOGRAM(S)



Precautionary Statements

Prevention:	P260 - Do not breathe dust. P264 - Wash affected area thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.
Response:	P314 - Get medical attention if you feel unwell.
Storage:	Not prescribed
Disposal:	P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

IDH number: 466863

Product name: LOCTITE LB 8065 COPPER ANTI-SEIZE STICK known as C5-A® Copper Anti-Seize Stick

Other hazards Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO	64742-52-5	30 - 60
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 30
Copper	7440-50-8	10 - 30
Graphite	7782-42-5	10 - 30
calcium(2+) 12-hydroxyoctadecanoate	3159-62-4	1 - 5
Quartz (SiO ₂) "respirable particulates (reaches the alveoli)" (RCS) <0.1%	14808-60-7	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. Get medical attention.
Most important symptoms and effects (acute and delayed):	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
Indication of any immediate medical attention / special treatment needed:	Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Improper extinguishing agents:	Not available.
Special firefighting procedures:	None
Unusual fire or explosion hazards:	None

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Acrolein.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow product to enter sewer or waterways.

Clean-up methods:

Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. For large spills absorb onto inert absorbent material and place in sealed container for disposal. For small spills wipe up with paper towel and place in container for disposal. Scrape up as much material as possible. Clean residue with soap and water.

7. HANDLING AND STORAGE

Handling:

Wash thoroughly after handling. Avoid contact with eyes, skin and clothing. Keep container closed.

Storage:

Keep in a cool, well ventilated area.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Copper	0.2 mg/m3 TWA (as Cu) Fume. 1 mg/m3 TWA (as Cu) Dust and mist.	1 mg/m3 PEL (as Cu) Dust and mist. 0.1 mg/m3 PEL (as Cu) Fume.	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1%	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable 0.1 mg/m3 TWA Respirable	None	None

Engineering controls:	Use only with adequate ventilation. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Copper
Odor:	Mild, Petroleum
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not determined
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Density/Relative density:	1.18
Relative vapor density:	Not applicable, Product is a solid
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not determined
Flammability:	non flammable
Evaporation rate:	Not determined
Solubility:	Insoluble Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	0 %
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Acrolein.
Incompatible materials:	Oxidizing agents. Acids. Alkalis.
Reactivity:	Not available.
Conditions to avoid:	None known

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-----------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Inhalation of copper fumes may result in metal fume fever. Symptoms include metallic taste, discoloration of skin or hair. This product has low volatility and is not expected to cause respiratory tract irritation during normal conditions of use. May cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: May cause skin irritation.

Eye contact: May cause eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Hazardous Component(s)	LD50s and LC50s
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO	Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l
Copper	Inhalation LC50 (Rat, 4 h) = > 5.11 mg/l
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3
calcium(2+) 12-hydroxyoctadecanoate	None
Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1%	None

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO			
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant		
Copper	Irritant	Allergen	Blood Central nervous system Developmental Gastrointestinal Immune system Kidney Liver Mutagen Sensory Skin
Graphite			Lung
calcium(2+) 12-hydroxyoctadecanoate			
Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1%			

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Copper	No	No	No
Graphite	No	No	No
calcium(2+) 12-hydroxyoctadecanoate	No	No	No
Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1%	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper)
Hazard class or division: 9
Identification number: UN 3077
Packing group: III
Marine pollutant: Copper

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 1,2,3,4,5,8,9,10,11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/06/2025

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.