



Revision Number: 012.1

Issue date: 07/03/2025

**1. IDENTIFICATION**

|                                       |  |                             |  |
|---------------------------------------|--|-----------------------------|--|
| <b>Product name:</b>                  | <b>LOCTITE SI 598 BK known as RTV 598 Black Silicone - 80ml</b>                        | <b>IDH number:</b>          | 866849   |
| <b>Product type/ Recommended use:</b> | Silicone sealant   | <b>Item number:</b>         | 41241  |
| <b>Restriction of Use:</b>            | None identified  | <b>Region:</b>              | Canada   |
| <b>Company address:</b>               | Henkel Canada Corporation<br>Meadowpine Boulevard 2515<br>Mississauga, Ontario L5N 6C3 | <b>Contact information:</b> | Telephone: +1 (905) 814-6511<br>MEDICAL EMERGENCY Phone: Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711<br>TRANSPORT EMERGENCY Phone: CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887<br>MEDICAL EMERGENCY Phone: Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711<br>TRANSPORT EMERGENCY Phone: CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887<br>Internet: www.henkelna.com |

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.  
H319 - CAUSES SERIOUS EYE IRRITATION.  
H351 - SUSPECTED OF CAUSING CANCER.  
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| EYE IRRITATION                                     | 2A              |
| SKIN SENSITIZATION                                 | 1               |
| CARCINOGENICITY                                    | 2               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |

**PICTOGRAM(S)**



**Precautionary Statements**

|                    |  |
|--------------------|--|
| <b>Prevention:</b> | P201 - Obtain special instructions before use.<br>P202 - Do not handle until all safety precautions have been read and understood.<br>P260 - Do not breathe dust.<br>P264 - Wash affected area thoroughly after handling.<br>P272 - Contaminated work clothing should not be allowed out of the workplace. |
| <b>Response:</b>   | P280 - Wear protective gloves, clothing, eye and face protection.<br>P302+P352 - IF ON SKIN: Wash with plenty of water.<br>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.                               |

IDH number: 866849

Product name: LOCTITE SI 598 BK known as RTV 598 Black Silicone - 80ml

**Storage:**  
**Disposal:**

P308+P313 - IF exposed or concerned: Get medical attention.  
P333+P313 - If skin irritation or rash occurs: Get medical attention.  
P337+P313 - If eye irritation persists: Get medical attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Other hazards** Not available.

Classification complies with Canadian Hazardous Products Regulations and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                                   | CAS Number | Weight %* |
|--|------------|-----------|
| Limestone  | 1317-65-3  | 30 - 60   |
| Silane, dichlorodimethyl-, reaction products with silica | 68611-44-9 | 5 - 10    |
| Butan-2-one O,O',O"- (vinylsilylydyne)trioxime           | 2224-33-1  | 1 - 5     |
| 2-butanone oxime   | 96-29-7    | 1 - 5     |
| Quartz (SiO <sub>2</sub> )                               | 14808-60-7 | 0.1 - 1   |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

|  |  |
|--|--|
| <b>Inhalation:</b>   | Move to fresh air in case of accidental inhalation of vapours or decomposition products. If symptoms develop and persist, get medical attention.   |
| <b>Skin contact:</b>   | Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.                                 |
| <b>Eye contact:</b>  | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If adverse health effects develop seek medical attention. |
| <b>Ingestion:</b>  | Do not induce vomiting. In case of adverse health effects seek medical advice.   |
| <b>Most important symptoms and effects (acute and delayed):</b>                  | The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.                     |
| <b>Indication of any immediate medical attention / special treatment needed:</b> | Not available.   |

### 5. FIRE FIGHTING MEASURES

|   |   |
|---|---|
| <b>Extinguishing media:</b>               | Foam, dry chemical or carbon dioxide. Water spray or fog.                       |
| <b>Improper extinguishing agents:</b>     | Not available.  |
| <b>Special firefighting procedures:</b>   | Wear self contained breathing apparatus. Prevent inhalation of fumes and gases. |
| <b>Unusual fire or explosion hazards:</b> | None  |

**Hazardous combustion products:** Oxides of silicon. Oxides of carbon. Formaldehyde. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

**Clean-up methods:** Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.

**Storage:** For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F) Store in a dry area below 90° F. Keep container closed.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|-----------|----------|-----------|-------|
| None                   | None      | None     | None      | None  |

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

**Eye/face protection:** Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Paste  
**Color:** Black  
**Odor:** Mild  
**Odor threshold:** Not available.  
**pH:** Not applicable, Product is non-soluble (in water).  
**Vapor pressure:** < 5 mm hg (20 °C (68°F))  
**Boiling point/range:** Not applicable, Decomposes before boiling point is reached  
**Melting point/ range:** Not applicable, Determination technically not possible  
**Density/Relative density:** 1.3 at 20 °C (68°F)  
**Relative vapor density:** 20 °C Heavier than air.  
**Flash point:** > 93 °C (> 199.4 °F) Tagliabue closed cup  
**Flammable/Explosive limits - lower:** Not available.  
**Flammable/Explosive limits - upper:** Not available.  
**Autoignition temperature:** Not available.  
**Flammability:** Not applicable  
**Evaporation rate:** Not available.  
**Solubility:** Insoluble Water

|   |                                     |
|---|-------------------------------------|
| <b>Partition coefficient n-octanol/water (logarithmic value):</b> | Not available.                      |
| <b>VOC content:</b>   | 2.27 %                              |
| <b>Dynamic viscosity:</b>   | Not available.                      |
| <b>Kinematic viscosity:</b>                                       | Not available.                      |
| <b>Particle characteristics:</b>                                  | Not applicable, mixture is a paste. |
| <b>Decomposition temperature:</b>                                 | Not available.                      |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable at normal conditions.   |
| <b>Hazardous reactions:</b>              | None under normal processing.  |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Oxides of silicon. Formaldehyde. Methyl ethyl ketoxime formed during cure. |
| <b>Incompatible materials:</b>           | Oxidizing agents. Acids and bases.   |
| <b>Reactivity:</b>                       | Not available.   |
| <b>Conditions to avoid:</b>              | Exposure to moisture.  |

## 11. TOXICOLOGICAL INFORMATION

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Likely routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-----------------------------------|-----------------------------------|

**Potential Health Effects/Symptoms**

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

**Skin contact:** May cause skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s)                                   | LD50s and LC50s                          |
|--|--|
| Limestone  | None                                     |
| Silane, dichlorodimethyl-, reaction products with silica | None                                     |
| Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime            | None                                     |
| 2-butanone oxime   | Inhalation LC50 (Rat, 4 h) = > 4.83 mg/l |
| Quartz (SiO2)  | None                                     |

| Hazardous Component(s)                                   | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects  |
|--|--------------------------|------------------------|---|
| Limestone  | Nuisance dust            |                        |   |
| Silane, dichlorodimethyl-, reaction products with silica |                          |                        |   |
| Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime            | Irritant                 | Allergen               |   |
| 2-butanone oxime   | Irritant                 | Allergen               | Blood<br>Central nervous system<br>Eyes<br>Some evidence of carcinogenicity |
| Quartz (SiO2)  |                          |                        | Immune system<br>Lung<br>Some evidence of carcinogenicity                   |

| Hazardous Component(s)                                   | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Limestone  | No                            | No              | No                                       |
| Silane, dichlorodimethyl-, reaction products with silica | No                            | No              | No                                       |
| Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime            | No                            | No              | No                                       |
| 2-butanone oxime   | No                            | No              | No                                       |
| Quartz (SiO2)  | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

**12. ECOLOGICAL INFORMATION**

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Exceptions:** None

## 15. REGULATORY INFORMATION

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 9,11,15

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 07/03/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.